

|                             |   |
|-----------------------------|---|
| Drive chain.....            | Slack 35 ~ 40 mm (1.4 ~ 1.6 in.).   |
| Nuts, bolts, fasteners..... | Check that steering and suspension components, axles, and all controls are properly tightened or fastened.  |
| Steering.....               | Action smooth but not loose from lock to lock. No binding of control cables.  |
| Brakes.....                 | Brake pad wear: Lining thickness more than 1 mm (0.04 in.) left.<br>No brake fluid leakage.<br>Brake pedal play 20 ~ 30 mm (0.8 ~ 1.2 in.)<br>Brake lining wear: Indicator within "USABLE RANGE". |
| Throttle.....               | Throttle grip play 2 ~ 3 mm (0.08 ~ 0.12 in.).  |
| Clutch.....                 | Clutch lever play 2 ~ 3 mm (0.08 ~ 0.12 in.).<br>Clutch lever operates smoothly.  |
| Coolant.....                | No coolant leakage<br>Coolant level between level lines (when engine is cold).  |
| Electrical equipment.....   | All lights and horn work.   |
| Engine stop switch.....     | Stops engine.   |
| Side and center stands..... | Return to their fully up position by spring tension.<br>Return springs not weak or not damaged.   |

Refer to "Daily Safety Checks" caution label attached to the back of the left side cover.