


# LAMIBIND 340 HM



## Available Options



Side Gluing Rollers



Milling Disk



Touch-Screen



Standard Glue Tank



Slitting Knives

The Lamibind 340 Hot-Melt semi automatic bookbinding machine is easy to handle, simple bookbinder machine, which is excellently suitable for binding office documents, ideally suited for short run A4-A5 books. It has an electric carriage closing/clamping, slitting unit and electric binding unit. All these functions are done automatically by the machine. The machine possesses with binding timer and automatic return of carriage clamp. With its user friendly touch-screen this machine helps every operator to make professional quality books very easily. Reliable components are the backbone of every great machine; therefore we have implemented the most stable electronics and electrical components available to us.

Maximum document thickness is 40mm (1,51")  
Maximum document length is 340mm (13,3")



OF THE 2015

## RIGO

Tool and Mould  
Production Ltd.

Tel: (36) 56 580-031  
Fax: (36) 56 580-032  
E-mail: [rigokft@rigokft.hu](mailto:rigokft@rigokft.hu)  
Web: [www.rigokft.hu](http://www.rigokft.hu)

Headquarter: H-1221, Budapest, Orsovai Street 3.  
Mailing address: H-5435, Martfű, Gesztenye Sor 1.  
Settlement: H-5430, Tiszaföldvár Kossuth Street 119.



# LAMIBIND 340 HM

Specifications	340 ECO	340 ADVANCED
Dimensions of the machine (l x w x h mm)	1400x825x1057	
(l x w x h inch)	55"x32"x41"	
Package of the machine (l x w x h mm)	1600x1025x1300	
(l x w x h inch)	62"40"x51"	
Net weight (kg)	300	
Gross weight (kg)	340	
Power supply (elective)	1~230 V-50 Hz / 200-220 V-60 Hz / 100-120 V 60Hz	
Nominal current (A)	12 / 14 / 25	
Capacity (kW)	3	
Compressed air supply (bar)	Not necessary	
Lenght of the bound document (mm/inch)	80-340	
Thickness of the bound document (mm/inch)	1-40	
Theoretical number of working cycles (fwd-bwd/hour) * The abobe value is theoretical number of the working cycles. The real speed and quantity of books can be bound on the machine depends on the strenght features of the flue used on the machine, the necessary binding/nipping time, the thickness of the document to be bound, deoends on the skill and quickness of the machine operator, and the selected binding technology.	290*	
Adjustment of the binding time of the document	1-99	
Binding cycle counter	Yes	
<b>Milling unit</b>		
Spine preperation	<b>Fixed Notching</b>	<b>Fixed Milling &amp; Notching</b>
<b>Gluing unit</b>		
Heat-up time; depending of the type of glue is used on the machine (minute)	30-45	
Temperature range of the melting of the glue (C/F)	100-200	
Volume of the glue container	1 kg	2 kg
Possibility to use different type of spine and side glue & side gluing rollers	<b>Not available</b>	<b>Standard</b>
Standby mode	Yes	
<b>Binding unit</b>		
Possibility to adjust the position of the book block over the binding unit	Yes	
<b>Other Functions</b>		
User Interface	Touch Screen	
Operating software	RIGO	
Software update	Option	Yes
Online remote control		Yes
<b>Options</b>		
Tape binding	Option	
Automatic start of the carriage clamp	Option	
Magnetic book holder	Option	
Paper dust extraction	Option	Standard
Glue fume extractor unit	Option	
Large cover holder	Option	
Cover sensor	Not available	Option
Side shelf	Option	

